

UNIT HEATERS & DUCT FURNACES

STERLING Model **GG** - Gas Fired Unit Heaters



Horizontal Low Profile

- 82%+ Efficient..
- Natural Gas, Spark Pilot Ignition.
- Power Vented.
- Concentric Venting Option (accessory vent kit required).
- 115/1 Power Supply with 24 Volt Gas Valve.
- Adjustable Horizontal Deflector.



Model	Capacity	Price Each	Weight
GG 030 A1NSA11	30	\$551	75
GG 045 A1NSA11	45	580	80
GG 060 A1NSA11	60	612	95
GG 075 A1NSA11	75	668	100
GG 090 A1NSA11	90	697	120
GG 120 A1NSA11	120	810	155

STERLING Model **TF** - Gas Fired Unit Heaters

Horizontal Propeller Style

- 83%+ Efficient.
- Natural Gas, Spark Pilot Ignition.
- Power Vented.
- Concentric Venting Option (accessory vent kit required).
- 115/1 Power Supply with 24 Volt Gas Valve.
- Adjustable Horizontal Deflector.



Model	Capacity	Price Each	Weight
TF 150 A1NS1110	150	\$853	195
TF 175 A1NS1110	175	970	241
TF 200 A1NS1110	200	1,057	251
TF 250 A1NS1110	250	1,166	261
TF 300 A1NS1110	300	1,372	367
TF 350 A1NS1110	350	1,634	381
TF 400 A1NS1110	400	1,718	395

Add Model T822K Single Stage Heating Low Volt T-stat \$53.00.

STERLING Model **QVES** - Gas Fired Duct Furnaces

Horizontal Indoor Duct Furnace

- 80% + efficient.
- Natural Gas, Spark Pilot ignition.
- Power Vented.
- 115/1 power supply w/ 24 volt gas valve.
- Combustion air pressure switch.
- Right Hand side access.
- 4 point suspension.



Model	Capacity	Price Each	Weight
QVES 100 A1N20A1	100	\$ 1,138.00	170
QVES 150 A1N20A1	150	1,236.00	194
QVES 175 A1N20A1	175	1,305.00	213
QVES 200 A1N20A1	200	1,349.00	229
QVES 250 A1N20A1	250	1,531.00	260
QVES 300 A1N20A1	300	1,814.00	309
QVES 350 A1N20A1	350	1,956.00	386
QVES 400 A1N20A1	400	2,087.00	400

Add Model T822K Single Stage Heating Low Volt T-stat \$53.00.



Sterling Unit Heaters are Factory Stock subject to availability. 2-3-day rush shipment also available.

INFRARED HEATERS



RE-VERBER-RAY® Low Intensity Tube Heaters by Detroit Radiant Products Company include features not provided by other manufactures that save installation time and money:

- ✓ Interlocking Swaged Radiant Tubes
- ✓ Power Cord Connection
- ✓ Tool Free Serviceability
- ✓ Sight Glass for Burner Inspection from Floor
- ✓ 1/2" Gas Cock & Stainless Steel Flexible Connector Provided
- ✓ Lower Clearance to Combustible Ratings



RE-VERBER-RAY® Infrared Heaters include these quality features:

- Highly Polished Aluminum Reflectors w/ End Caps.
- Reliable Hot Surface Ignition.
- Black Coated Titanium Stabilized or Aluminized Steel Combustion Chambers.

Model HL3 - Gas Fired Infrared Heaters

- 2-Stage (Hi-Lo) Burner Control
- 24V Control, Self-Diagnostic w/ LED Indicators
- Black Coated Aluminized Steel 16 Ga. Radiator.
- 5-Year Tube, 10-Year Burner Warranty.

Model XTS3 - Gas Fired Unit Heaters

- Single Stage Burner Control.
- 120V Control w/ Pre-purge
- Hot-Rolled Steel 16 Ga. Radiator
- 3-Year Tube, 5-Year Burner Warranty.

Model	20 Ft. Straight	40 Ft. Straight	60 Ft. Straight	"U" Section*	T-Stat	Remarks
HL3 (MBH)	\$1,115 (100)	\$1,422 (175)	\$1,774 (200)	\$180	\$179 #TH-109	"HLRP" relay required for multiple units on one T-stat.
XTS3 (MBH)	\$990 (75)	\$1,239 (150)	\$1,567 (175)	\$180	\$179 #TH-109	

* "U" section includes reflector.

Notes:

1. Above prices include chain sets and freight.
2. Heaters require field assembly.
3. Please contact your salesman for venting options and accessories.



Standard shipping lead time is 3 weeks. Call for rush shipment availability.



DETROIT RADIANT PRODUCTS COMPANY offers energy efficient heating solutions for commercial and industrial applications

Outdoor Heating - Wet Environments - High Performance LEED® Designs.

L. R. GORRELL COMPANY

PRICES SUBJECT TO CHANGE WITHOUT NOTICE! Minimum Order is \$35.00

MOTOR CONTROLS



At the heart of Sprecher + Schuh NEMA sized+ combination starters is the CATN7 and CATN6 line of contactors. These devices are compact yet sized according to NEMA standards for extended electrical life.

Sprecher + Schuh starters are equipped with state-of-the-art CEP7 solid state overload relays. The CEP7 offers accuracy, repeatability, phase-loss detection and selectable trip by dip-switch for Class 10, 15, 20, 30 time-overcurrent operation.

Non-combo starters are also available. Combination starters are available with Sprecher + Schuh LI0 disconnects (fusible or non-fusible) or with a Thermal-magnetic Molded Case Circuit Breakers (MCCB).

SPRECHER + SCHUH - CATN7 COMBINATION, FULL VOLTAGE NON-REVERSING STARTERS (FVNR)



Through-the-Door Combo Starters

- NEMA rated starters in NEMA 1 or NEMA 3R enclosures.
- NEMA-sized CAN7 contactor.
- CEP7 Electronic Overload Relay
- Control Circuit Transformer.
- Hand-Off-Auto (H-O-A) selector switch.
- Red Run pilot light.
- 2-NO and 1-NC auxiliaries.
- FH8 Fuse holder as fused primary of CCT
- Reset push button.

Also available with:

- Combo Starter / Disconnect with Non-Fusible Disconnect.
- Combo Starter / Disconnect with Fusible Disconnect (J-Type).
- Combo Starter / Disconnect with UL 489 600V class thermal-magnetic circuit breaker.

SPRECHER + SCHUH - FRACTIONAL MANUAL STARTER (FMS)

Sprecher + Schuh Fractional Manual Starters (FMS) consist of a snap switch combined with a thermal overload device operating on the solder-ratchet principle. To reset the overload mechanism, the switch lever is moved to the OFF position. The motor can be restarted by simply pushing the switch lever to the ON position. The switch is designed to prevent being held closed under a sustained motor overload.



FMS with Neon Pilot Light

Ratings (HP)		Poles	Type I (M1) General Purpose Surface Mounting Catalog Number	Price
115...230V AC	277V AC			
Toggle Switch Only				
1	1	1-Pole	FMS-TAX4	Call
1	1	2-Pole	FMS-TAX5	Call
Toggle Switch with Neon Pilot Light (115 or 230V)				
1	1	1-Pole	FMS-TAX216	Call
1	1	2-Pole	FMS-TAX109	Call

Notes:

Enclosed NEMA Starters are configured to meet your requirements and ship in 3 working days. Fractional Motors starters ship from factory stock.

Please contact your local LRG office for pricing!